



Available Finishes - Adaptor		
Antique Brass	Chrome	
Satin Nickel		
These valves have a highly polished finish.		

Available Finishes - Adaptor	
Old English Brass	Light Pewter
Unlacquered Brass	Pewter

These valves are unlacquered and designed to look old. They are hand finished and appearance may vary from one valve to the next

Allen Key size		
To adjust Lock-Shield	N/A	
To fit Coupler to Radiator	3/4"	
Allen Keys are not included		

Pressure RatingsMax Test Pressure12 BarMax Operating Pressure10 BarMax Differential Pressure1 BarPressure Drop Value (Kvs)1.6Kvs value is the metric measure for the flow of a fully opened

value is the metric measure for the flow of a fully opened valve. It is defined as: The volume flow in cubic metres per hour of water at a temperature of between 5° and 40° Celsius with a pressure drop across the valve of 1 bar.

Flow Ratings		
Normal Flow Rate	N/A	
Max Flow Rate	N/A	

Temperature Ratings		
Max Test Temperature	N/A	
Max Operating Temperature	N/A	
Temperature Adjustment Range	N/A	

Disclaimer

All dimensions are approximate and for roughing in only. We reserve the right to alter dimensions without notice. We recommend no work be carried out until the goods arrive. We can take no responsibility for errors in information supplied.

